















24 M. Wiertelowski et al.

4. Takasaki, M., Kotani, H., Mizuno, T., Nara, T.: Transparent surface acoustic wave tactile display. In: IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2005, pp. 3354–3359 (2005)
5. Biet, M., Giraud, F., Lemaire-Semail, B.: Squeeze film effect for the design of an ultrasonic tactile plate. *IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control* 54(12), 2678–2688 (2007)
6. Winfield, L., Glassmire, J., Colgate, J.E., Peshkin, M.: T-PaD: tactile pattern display through variable friction reduction. In: Second Joint EuroHaptics Conference and Symposium on Haptic Interfaces for Virtual Environment and Teleoperator Systems. *World Haptics*, pp. 421–426 (2007)
7. Smith, A.M., Chapman, E.C., Deslandes, M., Langlais, J.S., Thibodeau, M.P.: Role of friction and tangential force variation in the subjective scaling of tactile roughness. *Experimental Brain Research* 144(2), 211–223 (2002)
8. Smith, A.M., Basile, G., Theriault-Groom, J., Fortier-Poisson, P., Campion, G., Hayward, V.: Roughness of simulated surfaces examined with a haptic tool; effects of spatial period, friction, and resistance amplitude. *Experimental Brain Research* 202(1), 33–43 (2010)
9. Maeno, T., Otokawa, K., Konyo, M.: Tactile display of surface texture by use of amplitude modulation of ultrasonic vibration. In: *IEEE Ultrasonics Symposium*, pp. 62–65 (2006)
10. Hogan, N.: Impedance control: An approach to manipulation. *Journal of Dynamic Systems, Measurements, and Control* 107, 1–7 (1985)
11. Campion, G., Hayward, V.: Fast calibration of haptic texture synthesis algorithms. *IEEE Transactions on Haptics* 2(2), 85–93 (2009)